



Product No.	Thread	Dimensions (mm)					Number of Keyways	Weight (kg)
	d _{2G}	D _m	b ₁	D _a	m	n		
HM 42 T	Tr210 x 4	270	30	238	20	10	4 or 8	4,75
HM 44 T	Tr220 x 4	280	32	250	20	10	4 or 8	5,30
HM 46 T	Tr230 x 4	290	34	260	20	10	4 or 8	5,80
HM 48 T	Tr240 x 4	300	34	270	20	10	4 or 8	6,15
HM 50 T	Tr250 x 4	320	36	290	20	10	4 or 8	7,00
HM 52 T	Tr260 x 4	330	36	300	24	12	4 or 8	8,40
HM 54 T	Tr270 x 4	340	36	310	24	12	8	9,20
HM 56 T	Tr280 x 4	350	36	320	24	12	8	9,60
HM 58 T	Tr290 x 4	365	36	335	24	12	8	10,30
HM 60 T	Tr300 x 4	370	36	340	24	12	8	10,30
HM 62 T	Tr310 x 5	380	36	350	24	12	8	10,30
HM 64 T	Tr320 x 5	400	40	370	24	12	8	12,00
HM 66 T	Tr330 x 5	410	40	380	28	15	8	13,80
HM 68 T	Tr340 x 5	420	42	390	28	15	8	14,60
HM 70 T	Tr350 x 5	430	42	400	28	15	8	15,40
HM 72 T	Tr360 x 5	440	45	410	28	15	8	16,50
HM 74 T	Tr370 x 5	450	45	420	28	15	8	17,40
HM 76 T	Tr380 x 5	470	45	430	32	18	8	20,20
HM 80 T	Tr400 x 5	500	46	460	32	18	8	23,80
HM 84 T	Tr420 x 5	520	49	480	32	18	8	26,60
HM 88 T	Tr440 x 5	540	51	500	36	20	8	28,80
HM 92 T	Tr460 x 5	550	53	510	36	20	8	28,80
HM 96 T	Tr590 x 5	590	56	540	36	20	8	37,50