




AX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys, DIN 2215 / ISO 4184.



Li: Inner length / La: Outer length = Li + 50 mm / Ld: Norm length = Li + 30 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
AX 20	510	AX 42,5	1075	AX 73	1855
AX 21	535	AX 43	1100	AX 74	1880
AX 22	560	AX 44	1120	AX 75	1900
AX 23	585	AX 45	1145	AX 76	1930
AX 23,5	600	AX 45,5	1150	AX 77	1960
AX 24	610	AX 46	1170	AX 78	1980
AX 25	630	AX 46,5	1180	AX 79	2000
AX 26	660	AX 47	1200	AX 80	2032
AX 26,5	670	AX 47,5	1215	AX 81	2060
AX 27	685	AX 48	1220	AX 82	2085
AX 27,5	700	AX 48,5	1225	AX 83	2110
AX 28	710	AX 49	1250	AX 83,5	2120
AX 29	730	AX 50	1270	AX 84	2135
AX 29,5	750	AX 51	1300	AX 85	2160
AX 30	765	AX 52	1320	AX 86	2180
AX 31	785	AX 53	1350	AX 87	2210
AX 31,5	800	AX 54	1375	AX 88	2240
AX 32	815	AX 55	1400	AX 91	2310
AX 32,5	825	AX 56	1420	AX 92	2335
AX 33	840	AX 57	1450	AX 93	2360
AX 34	865	AX 58	1475	AX 96	2440
AX 34,5	875	AX 59	1500	AX 97	2465
AX 35	890	AX 60	1525	AX 98	2490
AX 35,5	900	AX 61	1550	AX 104	2640
AX 36	915	AX 62	1575	AX 109	2770
AX 37	940	AX 63	1600	AX 110	2795
AX 37,5	950	AX 64	1625	AX 118	3000
AX 38	965	AX 65	1650	AX 120	3050
AX 38,5	975	AX 66	1675	AX 132	3350
AX 39	990	AX 67	1700	AX 140	3560
AX 40	1015	AX 68	1725		
AX 41	1040	AX 69	1750		
AX 41,5	1050	AX 70	1775		
AX 42	1060	AX 71	1800		