


## AX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys,  
DIN 2215 / ISO 4184. Temperature from -40°C to +70°C.



Li: Inner length / La: Outer length = Li + 50 mm / Ld: Norm length = Li + 30 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
AX 20	508	AX 42	1067	AX 70	1778
AX 21	534	AX 42,5	1080	AX 71	1803
AX 22	559	AX 43	1092	AX 72	1829
AX 23	584	AX 44	1118	AX 73	1854
AX 23,5	597	AX 45	1143	AX 74	1880
AX 24	610	AX 45,5	1156	AX 75	1905
AX 25	635	AX 46	1168	AX 76	1930
AX 26	660	AX 46,5	1181	AX 77	1956
AX 26,5	673	AX 47	1194	AX 78	1981
AX 27	686	AX 47,5	1207	AX 79	2007
AX 27,5	699	AX 48	1219	AX 80	2032
AX 28	711	AX 48,5	1232	AX 81	2057
AX 29	737	AX 49	1245	AX 82	2083
AX 29,5	749	AX 50	1270	AX 83	2108
AX 30	762	AX 51	1295	AX 83,5	2121
AX 31	787	AX 52	1321	AX 84	2134
AX 31,5	800	AX 53	1346	AX 85	2159
AX 32	813	AX 54	1372	AX 86	2184
AX 32,5	826	AX 55	1397	AX 87	2210
AX 33	838	AX 56	1422	AX 88	2235
AX 34	864	AX 57	1448	AX 91	2311
AX 34,5	876	AX 58	1473	AX 92	2337
AX 35	889	AX 59	1499	AX 93	2362
AX 35,5	902	AX 60	1524	AX 96	2438
AX 36	914	AX 61	1549	AX 97	2464
AX 37	940	AX 62	1575	AX 98	2489
AX 37,5	953	AX 63	1600	AX 104	2642
AX 38	965	AX 64	1626	AX 109	2769
AX 38,5	978	AX 65	1651	AX 110	2794
AX 39	991	AX 66	1676	AX 118	2997
AX 40	1016	AX 67	1702	AX 120	3048
AX 41	1041	AX 68	1727	AX 132	3353
AX 41,5	1054	AX 69	1753	AX 140	3556