




BX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys,
DIN 2215 / ISO 4184. Temperature from -40°C to +70°C.



Li: Inner length / La: Outer length = Li + 69 mm / Ld: Norm length = Li + 40 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
BX 23	584	BX 48	1219	BX 78	1981	BX 107	2718
BX 24	610	BX 49	1245	BX 79	2007	BX 108	2743
BX 25	635	BX 50	1270	BX 80	2032	BX 109	2767
BX 26	660	BX 51	1295	BX 81	2057	BX 110	2794
BX 26,5	673	BX 52	1321	BX 82	2083	BX 111	2819
BX 28	711	BX 52,5	1334	BX 83	2108	BX 112	2845
BX 29	737	BX 53	1346	BX 83,5	2121	BX 113	2870
BX 30	762	BX 54	1372	BX 84	2134	BX 114	2896
BX 31	787	BX 55	1397	BX 85	2159	BX 115	2921
BX 32	813	BX 56	1422	BX 86	2184	BX 116	2946
BX 32,5	826	BX 57	1448	BX 87	2210	BX 117	2972
BX 33	838	BX 58	1473	BX 88	2235	BX 118	2997
BX 34	864	BX 59	1499	BX 89	2261	BX 119	3023
BX 34,5	876	BX 60	1524	BX 90	2286	BX 120	3048
BX 35	889	BX 61	1549	BX 91	2311	BX 121	3073
BX 36	914	BX 62	1575	BX 92	2337	BX 122	3099
BX 37	940	BX 63	1600	BX 93	2362	BX 124	3150
BX 38	965	BX 64	1626	BX 94	2388	BX 125	3175
BX 39	991	BX 65	1651	BX 95	2413	BX 126	3200
BX 40	1016	BX 66	1676	BX 96	2438	BX 128	3251
BX 41	1041	BX 67	1702	BX 96,5	2451	BX 130	3302
BX 41,5	1054	BX 68	1727	BX 97	2464	BX 132	3353
BX 42	1067	BX 69	1753	BX 98	2489	BX 133	3378
BX 42,5	1080	BX 70	1778	BX 99	2515	BX 134	3404
BX 43	1092	BX 71	1803	BX 100	2540	BX 135	3429
BX 44	1118	BX 72	1829	BX 101	2565	BX 136	3454
BX 45	1143	BX 73	1854	BX 102	2591	BX 138	3505
BX 45,5	1156	BX 74	1880	BX 103	2616	BX 139	3531
BX 46	1168	BX 75	1905	BX 104	2642	BX 140	3556
BX 46,5	1181	BX 76	1930	BX 105	2667	BX 144	3658
BX 47	1194	BX 77	1956	BX 106	2692	BX 152	3861
						BX 158	4013