




BX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys, DIN 2215 / ISO 4184.



Li: Inner length / La: Outer length = Li + 69 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
BX 23	585	BX 51	1300	BX 83,5	2120	BX 116	2950
BX 24	615	BX 52	1320	BX 84	2135	BX 117	2970
BX 25	630	BX 52,5	1335	BX 85	2160	BX 118	3000
BX 26	660	BX 53	1350	BX 86	2185	BX 119	3025
BX 26,5	670	BX 54	1370	BX 87	2210	BX 120	3050
BX 28	710	BX 55	1400	BX 88	2235	BX 121	3075
BX 29	735	BX 56	1420	BX 89	2260	BX 122	4000
BX 30	750	BX 57	1450	BX 90	2285	BX 124	3150
BX 31	785	BX 58	1475	BX 91	2310	BX 125	3175
BX 32	815	BX 59	1500	BX 92	2335	BX 126	3200
BX 32,5	825	BX 60	1525	BX 93	2360	BX 128	3250
BX 33	840	BX 61	1550	BX 94	2390	BX 130	3300
BX 34	865	BX 62	1575	BX 95	2415	BX 132	3350
BX 34,5	875	BX 63	1600	BX 96	2440	BX 133	3380
BX 35	890	BX 64	1625	BX 96,5	2450	BX 134	3405
BX 36	915	BX 65	1650	BX 97	2465	BX 135	3430
BX 37	940	BX 66	1675	BX 98	2490	BX 136	3455
BX 38	965	BX 67	1700	BX 99	2415	BX 138	3505
BX 39	990	BX 68	1725	BX 100	2540	BX 139	3530
BX 40	1015	BX 69	1750	BX 101	2565	BX 140	3555
BX 41	1040	BX 70	1780	BX 102	2590	BX 144	3660
BX 41,5	1050	BX 71	1805	BX 103	2615	BX 152	3860
BX 42	1060	BX 72	1830	BX 104	2640	BX 158	4015
BX 42,5	1075	BX 73	1855	BX 105	2665		
BX 43	1090	BX 74	1880	BX 106	2690		
BX 44	1120	BX 75	1905	BX 107	2720		
BX 45	1150	BX 76	1930	BX 108	2445		
BX 45,5	1165	BX 77	1950	BX 109	2770		
BX 46	1175	BX 78	1980	BX 110	2795		
BX 46,5	1180	BX 79	2005	BX 111	2820		
BX 47	1200	BX 80	2030	BX 112	2845		
BX 48	1215	BX 81	2055	BX 113	2870		
BX 49	1250	BX 82	2080	BX 114	2900		
BX 50	1275	BX 83	2110	BX 115	2920		