




CX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys, DIN 2215 / ISO 4184.



Li: Inner length / La: Outer length = Li + 88 mm / Ld: Norm length = Li + 58 mm

Item No.	Li (mm)	Item No.	Li (mm)
CX 37,5	950	CX 102	2590
CX 39	975	CX 108	2750
CX 43	1090	CX 109	2770
CX 44	1120	CX 110	2800
CX 47	1200	CX 118	3000
CX 48	1215	CX 124	3150
CX 49	1250	CX 132	3350
CX 51	1295	CX 140	3550
CX 52	1320	CX 158	4015
CX 55	1400	CX 173	4395
CX 56	1420	CX 180	4570
CX 59	1500		
CX 60	1525		
CX 61	1550		
CX 62	1575		
CX 67	1700		
CX 68	1725		
CX 69	1750		
CX 70	1780		
CX 71	1805		
CX 72	1830		
CX 75	1905		
CX 76	1930		
CX 79	2000		
CX 80	2030		
CX 81	2060		
CX 85	2160		
CX 86	2185		
CX 88	2240		
CX 90	2285		
CX 93	2360		
CX 94	2390		
CX 96	2440		
CX 98	2500		