




CX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys,
DIN 2215 / ISO 4184. Temperature from -40°C to +70°C.



Li: Inner length / La: Outer length = Li + 88 mm / Ld: Norm length = Li + 58 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
CX 37,5	953	CX 67	1702	CX 93	2362
CX 39	991	CX 68	1727	CX 94	2388
CX 43	1092	CX 69	1753	CX 96	2438
CX 44	1118	CX 70	1778	CX 98	2489
CX 47	1194	CX 71	1803	CX 102	2590
CX 48	1219	CX 72	1829	CX 108	2743
CX 49	1245	CX 75	1905	CX 109	2769
CX 51	1295	CX 76	1930	CX 110	2794
CX 52	1321	CX 79	2007	CX 118	2997
CX 55	1397	CX 80	2032	CX 124	3150
CX 56	1422	CX 81	2057	CX 132	3353
CX 59	1499	CX 85	2159	CX 140	3556
CX 60	1524	CX 86	2184	CX 158	4013
CX 61	1549	CX 88	2235	CX 173	4394
CX 62	1575	CX 90	2286	CX 180	4572