




## SPZ - Wrapped V-Belt

Oil and heat resistant, antistatic, DIN 7753 / ISO 4184. Temperature from -40°C to +70°C.



Li: Inner length / La: Outer length = Li + 50 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
SPZ 487	450	SPZ 962	925	SPZ 1340	1303	SPZ 1987	1950
SPZ 512	475	SPZ 987	950	SPZ 1347	1310	SPZ 2000	1963
SPZ 562	525	SPZ 1000	963	SPZ 1362	1325	SPZ 2030	1993
SPZ 587	550	SPZ 1010	973	SPZ 1387	1350	SPZ 2037	2000
SPZ 612	575	SPZ 1012	975	SPZ 1400	1363	SPZ 2087	2050
SPZ 630	593	SPZ 1024	987	SPZ 1412	1375	SPZ 2120	2083
SPZ 637	600	SPZ 1032	995	SPZ 1420	1383	SPZ 2137	2100
SPZ 662	625	SPZ 1037	1000	SPZ 1437	1400	SPZ 2157	2120
SPZ 670	633	SPZ 1047	1010	SPZ 1462	1425	SPZ 2160	2123
SPZ 687	650	SPZ 1060	1023	SPZ 1487	1450	SPZ 2187	2150
SPZ 710	673	SPZ 1077	1040	SPZ 1500	1463	SPZ 2200	2163
SPZ 722	685	SPZ 1080	1043	SPZ 1512	1475	SPZ 2240	2203
SPZ 737	700	SPZ 1087	1050	SPZ 1537	1500	SPZ 2287	2250
SPZ 750	713	SPZ 1100	1063	SPZ 1562	1525	SPZ 2300	2263
SPZ 762	725	SPZ 1112	1075	SPZ 1587	1550	SPZ 2360	2323
SPZ 772	735	SPZ 1137	1100	SPZ 1600	1563	SPZ 2400	2363
SPZ 787	750	SPZ 1140	1103	SPZ 1612	1575	SPZ 2410	2373
SPZ 800	763	SPZ 1162	1125	SPZ 1637	1600	SPZ 2437	2400
SPZ 812	775	SPZ 1180	1143	SPZ 1662	1625	SPZ 2450	2413
SPZ 825	788	SPZ 1187	1150	SPZ 1687	1650	SPZ 2487	2450
SPZ 837	800	SPZ 1200	1163	SPZ 1700	1663	SPZ 2500	2463
SPZ 850	813	SPZ 1212	1175	SPZ 1737	1700	SPZ 2540	2503
SPZ 862	825	SPZ 1237	1200	SPZ 1762	1725	SPZ 2650	2613
SPZ 875	838	SPZ 1250	1213	SPZ 1787	1750	SPZ 2700	2663
SPZ 880	843	SPZ 1262	1225	SPZ 1800	1763	SPZ 2737	2700
SPZ 887	850	SPZ 1270	1233	SPZ 1812	1775	SPZ 2800	2763
SPZ 900	863	SPZ 1282	1245	SPZ 1837	1800	SPZ 2900	2863
SPZ 912	875	SPZ 1287	1250	SPZ 1862	1825	SPZ 3000	2963
SPZ 925	888	SPZ 1300	1263	SPZ 1887	1850	SPZ 3150	3113
SPZ 937	900	SPZ 1312	1275	SPZ 1900	1863	SPZ 3170	3133
SPZ 940	903	SPZ 1320	1283	SPZ 1937	1900	SPZ 3350	3313
SPZ 950	913	SPZ 1337	1300	SPZ 1957	1920	SPZ 3550	3513
						SPZ 3750	3713