




XPA - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys, DIN 7753 / ISO 4184.



Li: Inner length / La: Outer length = Li + 63 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
XPA 732	687	XPA 1400	1355	XPA 2207	2162
XPA 757	712	XPA 1407	1362	XPA 2240	2195
XPA 782	737	XPA 1432	1387	XPA 2300	2255
XPA 800	755	XPA 1450	1405	XPA 2360	2315
XPA 807	762	XPA 1457	1412	XPA 2432	2387
XPA 832	787	XPA 1482	1437	XPA 2482	2437
XPA 850	805	XPA 1500	1455	XPA 2500	2455
XPA 857	812	XPA 1507	1462	XPA 2607	2562
XPA 882	837	XPA 1532	1487	XPA 2650	2605
XPA 900	855	XPA 1557	1512	XPA 2800	2755
XPA 907	862	XPA 1582	1537	XPA 3000	2955
XPA 932	887	XPA 1600	1555	XPA 3150	3105
XPA 950	905	XPA 1607	1562	XPA 3350	3305
XPA 957	912	XPA 1632	1487	XPA 3550	3505
XPA 982	937	XPA 1657	1612		
XPA 1000	955	XPA 1682	1637		
XPA 1007	962	XPA 1700	1655		
XPA 1032	987	XPA 1707	1662		
XPA 1060	1015	XPA 1732	1687		
XPA 1082	1037	XPA 1757	1712		
XPA 1107	1062	XPA 1782	1737		
XPA 1120	1075	XPA 1800	1755		
XPA 1132	1087	XPA 1807	1762		
XPA 1180	1135	XPA 1832	1787		
XPA 1207	1162	XPA 1857	1812		
XPA 1232	1187	XPA 1882	1837		
XPA 1250	1205	XPA 1900	1855		
XPA 1257	1212	XPA 1907	1862		
XPA 1272	1227	XPA 1932	1887		
XPA 1307	1262	XPA 1982	1937		
XPA 1320	1275	XPA 2000	1955		
XPA 1332	1287	XPA 2082	2037		
XPA 1357	1312	XPA 2120	2075		
XPA 1382	1337	XPA 2132	2087		