




## ZX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys, DIN 2215 / ISO 4184. Temperature from -40°C to +70°C.



Li: Inner length / La: Outer length = Li + 19 mm / Ld: Norm length = Li + 11 mm

Item No.	Li (mm)	Item No.	Li (mm)	Item No.	Li (mm)
ZX 19	485	ZX 37	940	ZX 54	1370
ZX 23	585	ZX 38	965	ZX 55	1400
ZX 24	610	ZX 38,5	975	ZX 56	1420
ZX 25	630	ZX 39	990	ZX 57	1450
ZX 26	660	ZX 40	1015	ZX 58	1475
ZX 27	685	ZX 40,5	1030	ZX 59	1500
ZX 28	710	ZX 41,5	1050	ZX 61	1550
ZX 28,5	725	ZX 42	1060	ZX 62	1575
ZX 29	730	ZX 43	1090	ZX 63	1600
ZX 29,5	750	ZX 43,25	1100	ZX 64	1625
ZX 30	765	ZX 43,5	1105	ZX 67	1700
ZX 31	790	ZX 44	1120	ZX 68	1725
ZX 31,5	800	ZX 46	1170	ZX 71	1800
ZX 32	815	ZX 46,5	1180	ZX 75	1900
ZX 33	840	ZX 47	1195	ZX 79	2000
ZX 33,5	850	ZX 48	1225	ZX 83,5	2120
ZX 34	865	ZX 48,5	1230	ZX 88	2240
ZX 35	890	ZX 49	1250	ZX 93	2360
ZX 36	915	ZX 52	1320	ZX 98	2500