




## ZX - Cogged Raw Edge V-Belt

Oil and heat resistant, antistatic, suitable for small diameter pulleys, DIN 2215 / ISO 4184.



Li: Inner length / La: Outer length = Li + 19 mm / Ld: Norm length = Li + 11 mm

Item No.	Li (mm)	Item No.	Li (mm)
ZX 19	485	ZX 48	1225
ZX 23	585	ZX 48,5	1230
ZX 24	610	ZX 49	1250
ZX 25	630	ZX 52	1320
ZX 26	660	ZX 54	1370
ZX 27	685	ZX 55	1400
ZX 28	710	ZX 56	1420
ZX 28,5	725	ZX 57	1450
ZX 29	730	ZX 58	1475
ZX 29,5	750	ZX 59	1500
ZX 30	765	ZX 61	1550
ZX 31	790	ZX 62	1575
ZX 31,5	800	ZX 63	1600
ZX 32	815	ZX 64	1625
ZX 33	840	ZX 67	1700
ZX 33,5	850	ZX 68	1725
ZX 34	865	ZX 71	1800
ZX 35	890	ZX 75	1900
ZX 36	915	ZX 79	2000
ZX 37	940	ZX 83,5	2120
ZX 38	965	ZX 88	2240
ZX 38,5	975	ZX 93	2360
ZX 39	990	ZX 98	2500
ZX 40	1015		
ZX 40,5	1030		
ZX 41,5	1050		
ZX 42	1060		
ZX 43	1090		
ZX 43,25	1100		
ZX 43,5	1105		
ZX 44	1120		
ZX 46	1170		
ZX 46,5	1180		
ZX 47	1195		