



Housing No.	Shaft		Dimensions (mm)														Mounting Bolt	Weight (kg)	Labyrinth Seals	Bearing	Fixing Rings	End cover	O-Ring $\varnothing$ * Length	Grease Qty First filling
	da	db	Da	Ca	A	A1	A2	H	H1	H2	L	J	J1	N	N1	S								
<b>SD 2326 G</b>	130	150	280	108	230	180	240	333	170	70	510	430	100	34	28	14	M24	70	TS 34	22326	2 x FR 280-7,5	ETS36	4 x 520	1,1 kg
<b>SD 2328 G</b>	140	160	300	116	240	190	250	353	180	75	530	450	110	34	28	15	M24	78	TS 36	22328	2 X FR 300-7	ETS36	4 x 560	1,4 kg
<b>SD 2330 G</b>	150	170	320	124	260	210	270	375	190	80	560	480	120	34	28	10	M24	98	TS 38	22330	2 X FR 320-8	ETS38	4 x 590	1,8 kg
<b>SD 2332 G</b>	160	180	340	132	280	230	290	411	210	85	610	510	130	42	35	10	M30	123	TS 40	22332	2 x FR 340-9	ETS44	4 x 630	2,3 kg
<b>SD 2334 G</b>	170	190	360	140	290	240	300	434	220	90	640	540	140	42	35	12	M30	139	TS 48/190	22334	2 x FR 360-10	ETS48	4 x 660	3,0 kg
<b>SD 2338 G</b>	190	210	400	148	310	260	315	474	240	95	700	600	150	42	35	12	M30	187	TS 48/210	22338	2 x FR 400-8	ETS52	4 x 730	3,4 kg
<b>SD 2340 G</b>	200	220	420	166	320	280	330	516	260	100	770	650	160	50	42	13	M36	221	TS 56/220	22340	2 x FR 420-14	ETS60	4 x 770	4,9 kg
<b>SD 2344 G</b>	220	240	460	166	320	280	330	551	280	105	790	670	160	50	42	16	M36	252	TS 56/240	22344	2 x FR 460-10,5	ETS60	4 x 830	4,4 kg
<b>SD 2348 G</b>	240	260	500	180	350	310	360	591	300	110	830	710	190	50	42	22	M36	301	TS 60/260	22348	2 x FR 500-12,5	ETS60	4 x 900	6,2 kg
<b>SD 2352 G</b>	260	290	540	196	370	330	380	631	320	320	880	750	200	50	42	23	M36	339	TS 64/290	22352	2 X FR 540-15,5	ETS64	4 x 1010	7,7 kg
<b>SD 2356 G</b>	280	310	580	210	400	360	410	675	340	120	950	810	220	50	42	24	M36	427	TS 68/310	22356	2 X FR 580-17,5	ETS68	4 x 1080	9,4 kg

These Housings can also be manufactured of ductile iron or cast steel. Special kevlar or felt seals on request.