



Item No.	Dimensions (mm)					Recommended mounting bolt size
	N	N3	J4	J3	J6	
SSNHF 511-609 LH4	20	15	35	210	234	M12
SSNHF 512-610 LH4	20	15	35	210	234	M12
SSNHF 513-611 LH4	20	15	40	230	252	M12
SSNHF 515-612 LH4	20	15	40	230	257	M12
SSNHF 516-613 LH4	24	18	50	260	288	M16
SSNHF 517 LH4	24	18	50	260	292	M16
SSNHF 518-615 LH4	24	18	50	290	317	M16
SSNHF 519-616 LH4	24	18	50	290	317	M16
SSNHF 520-617 LH4	24	18	60	320	348	M16
SSNHF 522-619 LH4	24	18	70	350	378	M16
SSNHF 524-620 LH4	24	18	70	350	378	M16
SSNHF 526 LH4	28	22	70	380	414	M20
SSNHF 528 LH4	32	26	80	420	458	M24
SSNHF 530 LH4	32	26	90	450	486	M24
SSNHF 532 LH4	32	26	90	470	506	M24

See the catalogue [SNHF](#) for the remaining dimensions and standard two elongated mounting bolt holes (LH2).

See the catalogue [SSNHF + SNHF GS breaking loads](#) for breaking load data

Also available as two drilled round mounting bolt holes, version [SSNHF RH2](#).

Also available as four drilled round mounting bolt holes, version [SSNHF RH4](#).