



Bearing No.	Dimensions (mm)			Basic radial load rating (N)		Speed (1/min)		Weight (kg)
	d	D	B	Dynamic C_r	Static C_{or}	Limiting	Reference	
21304	20	52	15	36.450	30.150	15.000	12.000	0,16
21305	25	62	17	46.800	38.700	13.000	10.000	0,25
21306	30	72	19	64.800	56.700	11.000	8.500	0,39
21307	35	80	21	74.700	66.150	9.500	8.000	0,50
21308	40	90	23	97.200	95.400	7.500	7.000	0,70
21309	45	100	25	116.100	116.100	6.700	6.700	0,85
21310	50	110	27	116.100	116.100	6.700	6.300	1,28
21311	55	120	29	153.000	149.400	6.300	5.600	1,19
21312	60	130	31	190.800	205.200	6.300	4.500	1,78
21313	65	140	33	225.000	243.000	5.000	4.800	2,42
21314	70	150	35	225.000	243.000	5.000	4.800	3,00
21315	75	160	37	274.500	292.500	4.800	4.300	2,86
21316	80	170	39	274.500	292.500	4.800	4.300	2,65
21317	85	180	41	310.500	337.500	4.800	3.800	5,37
21318	90	190	43	342.000	373.500	4.500	3.600	6,26
21319	95	200	45	387.000	409.500	4.000	3.400	6,63
21320	100	215	47	441.000	477.000	3.600	3.200	8,19
21322	110	240	50	540.000	576.000	3.000	2.800	11,10