



Bearing No.	Dimensions (mm)			Basic radial load rating (kN)		Speed (1/min)		Weight (kg)
	d	D	B	Dynamic $C_r$	Static $C_{or}$	Limiting	Reference	
<b>23120</b>	100	165	52	405	513	4300	3000	4,2
<b>23122</b>	110	180	56	477	612	4000	2600	5,3
<b>23124</b>	120	200	62	567	720	3400	2400	7,4
<b>23126</b>	130	210	64	612	801	3000	2200	8,1
<b>23128</b>	140	225	68	684	909	2800	1900	9,8
<b>23130</b>	150	250	80	900	1197	2600	1700	15,0
<b>23132</b>	160	270	86	1044	1395	2400	1600	19,1
<b>23134</b>	170	280	88	1098	1521	2400	1500	20,7
<b>23136</b>	180	300	96	1278	1755	2200	1400	27,3
<b>23138</b>	190	320	104	1449	1998	2000	1300	35,3
<b>23140</b>	200	340	112	1499	2124	1700	1240	43,0
<b>23144</b>	220	370	120	1699	2475	1400	1060	55,2
<b>23148</b>	240	400	128	2080	3200	1300	970	67,3
<b>23152</b>	260	440	144	2398	3510	1200	850	92,5
<b>23156</b>	280	460	146	2506	3825	1100	780	99,5
<b>23160</b>	300	500	160	3031	4590	1100	720	131,0
<b>23164</b>	320	540	176	3531	5400	950	650	171,0
<b>23168</b>	340	580	190	4001	6120	900	590	217,0
<b>23172</b>	360	600	192	4064	6255	850	550	227,0
<b>23176</b>	380	620	194	4105	6390	800	510	241,0