



Item No.	Dimensions (mm)									Basic Load Ratings (kN)		Limiting Speed (RPM)		Weight (kg)
	d	D	T	B	C	r	da (max)	db (min)	Da (max)	Dynamic Radial	Static Radial	Grease	Oil	
30302	15	42	14,25	13	11	1	22	21	36	27,7	20	11300	15000	0,09
30303	17	47	15,25	14	12	1	25	23	41	34,2	25	9700	13000	0,13
30304	20	52	16,25	15	13	1,5	28	27	45	41,9	32,5	9000	12000	0,17
30305	25	62	18,25	17	15	1,5	34	32	55	55,3	43	7000	9500	0,26
30306	30	72	20,75	19	16	1,5	40	37	65	69,2	56	6000	8000	0,39
30307	35	80	22,75	21	18	2	45	44	71	88,9	73,5	5600	7500	0,51
30308	40	90	25,25	23	20	2	52	49	81	106	95	4700	6300	0,73
30309	45	100	27,25	25	22	2	59	54	91	132	120	4200	5600	0,97
30310	50	110	29,25	27	23	2,5	65	60	100	154	140	3900	5300	1,24
30311	55	120	31,5	29	25	2,5	71	65	110	176	163	3600	4800	1,56
30312	60	130	33,5	31	26	3	77	72	118	208	196	3200	4300	1,95
30313	70	140	36	33	28	3	83	77	128	240	228	3000	4000	2,42
30314	7	150	38	35	30	3	89	82	138	271	260	2800	3800	2,95
30315	75	160	40	37	31	3	95	87	148	301	290	2500	3400	3,49
30316	80	170	42,5	39	33	3	102	92	158	333	320	2400	3200	4,14
30317	85	180	44,5	41	34	4	107	99	166	372	365	2200	3000	4,84
30318	90	190	46,5	43	36	4	113	104	176	353	400	1900	2600	5,63
30319	95	200	49,5	45	38	4	118	109	186	353	390	1900	2600	6,46
30320	100	215	51,5	47	39	4	127	114	201	431	490	1800	2400	7,96
30321	105	225	53,5	49	41	4	132	119	211	462	530	1600	2200	9,08
30322	110	240	54,5	50	42	4	141	124	226	507	585	1600	2200	10,8
30324	120	260	59,5	55	46	4	152	134	246	601	710	1500	2000	13,7
30326	130	280	63,75	58	49	5	164	148	262	679	800	1300	1800	16,8
30328	140	300	67,75	62	53	5	176	158	282	690	730	1300	1800	20,1
30330	150	320	72	65	55	5	189	168	302	879	1060	1200	1600	24,8
30332	160	340	75	68	58	5	201	178	319	970	1180	1100	1500	28,9
30334	170	360	80	72	62	5	213	188	342	1040	1360	900	1300	35
30336	180	380	83	75	64	5	230	197	359	1120	1470	900	1200	41
30338	190	400	86	78	65	6	240	210	378	1210	1600	900	1200	46,7
30344	220	460	97	88	73	6	274	240	437	1440	1880	700	1000	67,9
30348	240	500	105	95	80	6	296	260	476	1780	2410	600	900	89,7
30352	260	540	113	102	85	7,5	320	286	508	2290	2600	600	800	105,5
30356	280	580	119	108	90	7,5	345	357	548	2700	3250	500	700	136