



Item No.	Dimensions (mm)									Basic Load Ratings (kN)		Limiting Speed (RPM)		Weight (kg)
	d	D	T	B	C	r	da (max)	db (min)	Da (max)	Dynamic Radial	Static Radial	Grease	Oil	
32004	20	42	15	15	12,0	0,5	25	25	37	25	27	9000	12000	0,10
320/22	22	44	15	15	11,5	0,5	27	27	39	26	29	8500	11000	0,10
32005	25	47	15	15	11,5	0,5	30	30	42	27	33	8000	11000	0,12
320/28	28	52	16	16	12,0	1,0	33	34	46	32	39	7100	9500	0,15
32006	30	55	17	17	13,0	1,0	35	36	49	36	45	6700	9000	0,17
320/32	32	58	17	17	13,0	1,0	38	39	50	38	47	6300	8500	0,19
32007	35	62	18	18	14,0	1,0	40	41	56	44	56	5600	8000	0,23
32008	40	68	19	19	14,5	1,0	46	46	62	53	71	5300	7100	0,28
32009	45	75	20	20	15,5	1,0	51	51	69	60	83	4500	6300	0,35
32010	50	80	20	20	15,5	1,0	56	56	74	61	87	4300	6000	0,38
32011	55	90	23	23	17,5	1,5	63	62	83	82	117	3800	5300	0,57
32012	60	95	23	23	17,5	1,5	67	67	88	86	127	3600	5000	0,61
32013	65	100	23	23	17,5	1,5	72	72	93	87	132	3400	4500	0,64
32014	70	110	25	25	19,0	1,5	78	77	103	104	158	3200	4300	0,87
32015	75	115	25	25	19,0	1,5	83	82	108	109	171	3000	4000	0,93
32016	80	125	29	29	22,0	1,5	89	87	117	140	222	2800	3600	1,32
32017	85	130	29	29	22,0	1,5	94	92	122	143	231	2600	3600	1,38
32018	90	140	32	32	24,0	1,5	100	99	131	170	273	2400	3200	1,78
32019	95	145	32	32	24,0	1,5	105	104	136	173	283	2400	3200	1,88
32020	100	150	32	32	24,0	1,5	109	109	141	176	294	2200	3000	1,95
32021	105	160	35	35	26,0	2,0	116	115	150	204	340	2000	2800	2,48
32022	110	170	38	38	29,0	2,0	122	120	160	236	390	2000	2600	3,09
32024	120	180	38	38	29,0	2,0	131	130	170	242	405	1800	2400	0,10
32026	130	200	45	45	34,0	2,0	144	140	190	320	534	1600	2200	5,07
32028	140	210	45	45	34,0	2,0	153	150	200	325	556	1600	2200	5,33
32030	150	225	48	48	36,0	2,0	164	162	213	375	650	1400	2000	6,61
32032	160	240	51	51	38,0	2,0	175	172	228	425	752	1300	1800	7,94
32034	170	260	57	57	43,0	2,0	187	182	248	505	890	1200	1700	10,61
32036	180	280	64	64	48,0	2,0	199	192	268	640	1130	1200	1600	14,31
32038	190	290	64	64	48,0	2,0	209	202	278	650	1170	1100	1500	14,91
32040	200	310	70	70	53,0	2,0	221	212	298	760	1371	1000	1400	18,92
32044	220	340	76	76	57,0	3,0	243	234	326	885	1611	950	1300	24,43
32048	240	360	76	76	57,0	3,0	261	254	346	920	1731	850	1200	26,23
32052	260	400	87	87	65,0	3,0	287	278	382	1160	2163	800	1100	38,54
32056	280	420	87	87	65,0	3,0	305	298	402	1180	2243	710	1000	40,64
32060	300	460	100	100	74,0	3,0	329	318	442	1441	2701	670	900	56,66
32064	320	480	100	100	74,0	3,0	350	338	462	1511	2910	630	850	60,06