



Item No.	Dimensions (mm)									Basic Load Ratings (kN)		Limiting Speed (RPM)		Weight (kg)
	d	D	T	B	C	r	da (max)	db (min)	Da (max)	Dynamic Radial	Static Radial	Grease	Oil	
33005	25	47	17	17	14,0	0,6	30	30	42	31,0	38,0	8.000	11.000	0,13
33006	30	55	20	20	16,0	1,0	35	36	49	42,0	54,0	6.700	9.000	0,21
33007	35	62	21	21	17,0	1,0	41	41	56	49,0	65,0	5.600	8.000	0,27
33008	40	68	22	22	18,0	1,0	46	46	62	59,0	81,5	5.300	7.100	0,32
33009	45	75	24	24	19,0	1,0	51	51	69	69,0	99,0	4.800	6.300	0,41
33010	50	80	24	24	19,0	1,0	56	56	74	70,5	104,0	4.300	6.000	0,45
33011	55	90	27	27	21,0	1,5	63	62	83	91,5	138,0	3.800	5.300	0,66
33012	60	95	27	27	21,0	1,5	67	67	88	96,0	150,0	3.600	5.000	0,71
33013	65	100	27	27	21,0	1,5	72	72	93	97,5	156,0	3.400	4.500	0,76
33014	70	110	31	31	25,5	1,5	78	77	103	127,0	204,0	3.000	4.300	1,11
33015	75	115	31	31	25,5	1,5	83	82	108	133,0	220,0	3.000	4.000	1,18
33016	80	125	36	36	29,5	1,5	90	87	117	172,0	282,0	2.800	3.600	1,66
33017	85	130	36	36	29,5	1,5	94	92	122	180,0	305,0	2.600	3.600	1,75
33018	90	140	39	39	32,5	2,0	100	99	131	220,0	360,0	2.400	3.200	2,21
33019	95	145	39	39	32,5	2,0	104	104	136	231,0	390,0	2.400	3.200	2,30
33020	100	150	39	39	32,5	2,0	108	109	141	235,0	405,0	2.200	3.000	2,38
33021	105	160	43	43	34,0	2,5	116	115	150	256,0	435,0	2.000	2.800	3,03
33022	110	170	47	47	37,0	2,5	123	120	160	294,0	515,0	2.000	2.600	3,84
33024	120	180	48	48	38,0	2,5	132	130	170	300,0	540,0	1.800	2.600	4,20
33026	130	200	55	55	43,0	2,5	143	140	190	395,0	715,0	1.700	2.200	6,25
33028	140	210	56	56	44,0	2,5	152	150	200	410,0	770,0	1.600	2.200	6,74
33030	150	225	59	59	46,0	3,0	164	162	213	435,0	805,0	1.400	2.000	8,07