



Outer ring with single split in axial direction.

Inner ring with cylindrical extensions at both sides.

Lubrication grooves and holes in the outer and inner rings.

Outer ring with lip seals in both sides.

Both outer and inner rings are properly phosphate treated.

Part No.	Dimensions (mm)									Load ratings (kN)		Weight (kg)
	d	d <sub>2</sub>	D	B	C	d <sub>k</sub>	R <sub>1S min</sub>	R <sub>2S min</sub>	α	dyn. C	stat. C0	
GE17HO.2RS	17	21,0	30	21	10	25,0	0,2	0,3	3	21,2	106	0,04
GE20HO.2RS	20	24,0	35	24	12	29,0	0,2	0,3	3	30	146	0,069
GE25HO.2RS	25	29,0	42	29	16	35,5	0,2	0,6	3	48	240	0,12
GE30HO.2RS	30	34,2	47	30	18	40,7	0,2	0,6	3	62	310	0,15
GE35HO.2RS	35	40,0	55	35	20	47,0	0,3	1,0	3	80	400	0,26
GE40HO.2RS	40	45,0	62	38	22	53,0	0,3	1,0	3	100	500	0,32
GE45HO.2RS	45	52,0	68	40	25	60,0	0,3	1,0	3	127	640	0,43
GE50HO.2RS	50	57,0	75	43	28	66,0	0,3	1,0	3	156	780	0,55
GE60HO.2RS	60	68,0	90	54	36	80,0	0,3	1,0	3	245	1220	1,1
GE70HO.2RS	70	78,0	105	65	40	92,0	0,3	1,0	3	315	1560	1,6
GE80HO.2RS	80	90,0	120	74	45	105,0	0,3	1,0	3	400	2000	2,5