



Outer ring pressed around inner ring.

Outer race lined with PTFE composite material

Spherical surface of inner ring hard chrome plated.

Material: Steel innerring, PTFE coated outerring.

Part No.	Dimensions (mm)									Load ratings (kN)		Weight (kg)
	d	D	B	C	d <sub>1</sub>	d <sub>k</sub>	R <sub>15 min</sub>	R <sub>25 min</sub>	α	dyn. C	stat. C0	
GE6UK	6	14	6	4	8	10	0,3	0,3	13	3,6	9,1	0,004
GE8UK	8	16	8	5	10	13	0,3	0,3	15	5,8	14	0,008
GE10UK	10	19	9	6	13	16	0,3	0,3	12	8,6	21	0,011
GE12UK	12	22	10	7	15	18	0,3	0,3	10	11	28	0,015
GE15UK	15	26	12	9	18	22	0,3	0,3	8	18	45	0,027
GE17UK	17	30	14	10	20	25	0,3	0,3	10	22	56	0,041
GE20UK	20	35	16	12	24	29	0,3	0,3	9	31	78	0,066
GE25UK	25	42	20	16	29	35,5	0,6	0,6	7	51	127	0,119
GE30UK	30	47	22	18	34	40,7	0,6	0,6	6	65	166	0,163