



Outer ring with single split in axial direction.

Outer race bonded with PTFE fabric.

Spherical surface of inner ring hard chrome plated.

Outer ring with lip seals in both sides.

Outer rings is properly phosphate treated.

Material: Steel innerring, PTFE coated outerring.

Part No.	Dimensions (mm)									Load ratings (kN)		Weight (kg)
	d	D	B	C	d ₁	d _k	R _{1s min}	R _{2s min}	α	dyn. C	stat. C0	
GE15UK.2RS	15	26	12	9	18	22	0,3	0,3	9	25	59	0,035
GE17UK.2RS	17	30	14	10	20	25	0,3	0,3	10	32	75	0,041
GE20UK.2RS	20	35	16	12	24	29	0,3	0,3	9	45	104	0,066
GE25UK.2RS	25	42	20	16	29	35,5	0,6	0,6	7	85	204	0,119
GE30UK.2RS	30	47	22	18	34	40,7	0,6	0,6	6	110	263	0,153
GE35UK.2RS	35	55	25	20	39	47	0,6	1	6	140	338	0,233
GE40UK.2RS	40	62	28	22	45	53	0,6	1	7	175	419	0,306
GE45UK.2RS	45	68	32	25	50	60	0,6	1	7	225	540	0,427
GE50UK.2RS	50	75	35	28	55	66	0,6	1	6	275	665	0,546
GE60UK.2RS	60	90	44	36	66	80	1	1	6	430	1030	1,040
GE70UK.2RS	70	105	49	40	77	92	1	1	6	550	1320	1,550
GE80UK.2RS	80	120	55	45	88	105	1	1	6	705	1700	2,310
GE90UK.2RS	90	130	60	50	98	115	1	1	5	860	2070	2,750
GE100UK.2RS	100	150	70	55	109	130	1	1	7	1070	2570	4,450
GE110UK.2RS	110	160	70	55	121	140	1	1	6	1150	2770	4,820
GE120UK.2RS	120	180	85	70	135	160	1	1	6	1680	4030	8,050
GE140UK.2RS	140	210	90	70	155	180	1	1	7	1890	4530	11,02
GE160UK.2RS	160	230	105	80	170	200	1	1	8	2400	5760	14,01
GE180UK.2RS	180	260	105	80	199	225	1,1	1,1	6	2700	6480	18,65
GE200UK.2RS	200	290	130	100	213	250	1,1	1,1	7	3750	9000	28,03
GE220UK.2RS	220	320	135	100	239	275	1,1	1,1	8	4120	9900	35,51
GE240UK.2RS	240	340	140	100	265	300	1,1	1,1	8	4500	10800	39,91
GE260UK.2RS	260	370	150	110	288	325	1,1	1,1	7	5360	12870	51,54
GE280UK.2RS	280	400	155	120	313	350	1,1	1,1	6	6300	15120	65,06
GE300UK.2RS	300	430	165	120	336	375	1,1	1,1	7	6750	16200	78,07