



Item No.	Dimensions (mm)														Mass (g)	M _A (Nm)	Load rating (N)			n _{DG} (1/min)		
	D	de	B	B1 max	B2	Be	C	C1	d1	d2	e	G	IG	r _{min}			W1	W2	C _{r w}		C _{0r w}	C _{ur w}
KRVE16PP	16	9	28	12,2	16	7	11	0,6	6	12,5	0,5	M6X1	8	0,15	-	-	20	3	4900	6600	950	3800
KRVE19PP	19	11	32	12,2	20	9	11	0,6	8	15	0,5	M8X1,25	10	0,15	-	-	32	8	5400	8000	1170	3100
KRVE22PP	22	13	36	13,2	23	10	12	0,6	10	17,5	0,5	M10X1	12	0,3	5	-	47	15	6200	9200	1210	2600
KRVE26PP	26	13	36	13,2	23	10	12	0,6	10	17,5	0,5	M10X1	12	0,3	5	-	62	15	7300	11500	1500	2600
KRVE30PP	30	15	40	15,2	25	11	14	0,6	12	23	0,5	M12X1,5	13	0,6	6	-	93	22	9500	14900	2050	2100
KRVE32PP	32	15	40	15,2	25	11	14	0,6	12	23	0,5	M12X1,5	13	0,6	6	-	104	22	10000	16100	2200	2100
KRVE35PP	35	20	52	19,5	32,5	14	18	0,8	16	27,6	1	M16X1,5	17	0,6	8	-	177	58	12600	23100	3200	1600
KRVE40PP	40	22	58	21,6	36,5	16	20	0,8	18	31,5	1	M18X1,5	19	1	8	8	255	87	14700	26500	3500	1400
KRVE47PP	47	24	66	25,6	40,5	18	24	0,8	20	36,5	1	M20X1,5	21	1	10	10	400	120	20300	42000	5900	1300
KRVE52PP	52	24	66	25,6	40,5	18	24	0,8	20	36,5	1	M20X1,5	21	1	10	10	473	120	22300	48000	6700	1300
KRVE62PP	62	28	80	30,6	49,5	22	29	0,8	24	44	1	M24X1,5	25	1	14	14	789	220	33500	75000	11200	1100
KRVE72PP	72	28	80	30,5	49,5	22	29	0,8	24	44	1	M24X1,5	25	1,1	14	14	1038	220	36500	85000	12600	1100
KRVE80PP	80	35	100	37	63	29	35	1	30	53	1,5	M30X1,5	32	1,1	14	-	1665	450	48500	117000	17400	850
KRVE90PP	90	35	100	37	63	29	35	1	30	53	1,5	M30X1,5	32	1,1	14	14	2032	450	52000	129000	19000	850

Legend:

- de** Eccentric collar, tolerance: h9
- d1** Tolerance: h7
- e** Maximum eccentric collar offset
- W** Nominal dimension for hexagonal socket
- M_A** Nut tightening torque
- C_{r w}** Effective dynamic load rating as track roller (radial)
- C_{0r w}** Effective static load rating as track roller (radial)
- C_{ur w}** Fatigue limit load
- n_{DG}** Speed (with continuous operation and grease lubrication)

Lubrication nipple:

Every item is shipped with a drive fit lubrication nipple and a plug.

