


Legend:

- Crw** Effective dynamic load rating as track roller (radial)
- C0rw** Effective static load rating as track roller (radial)
- Fr per** Permissible dynamic radial load
- F0 per** Permissible static radial load
- Curw** Fatigue limit load
- nDG** Speed (with continuous operation and grease lubrication)

Part No.	Dimensions (mm)							Mass g	Load rating(N)					nDG (1/min)
	d	D	B	C	d2	r1min	rmin		Crw	C0rw	Fr per	F0r per	Curw	
PWTR15.2RS	15	35	19	18	20	0,3	0,6	99	12600	14900	10600	14900	1790	6000
PWTR1542.2RS	15	42	19	18	20	0,3	0,6	158	14700	16200	16200	16200	2180	6000
PWTR17.2RS	17	40	21	20	22	0,5	1,0	147	14300	18200	16400	18200	2200	5000
PWTR1747.2RS	17	47	21	20	22	0,5	1,0	220	15900	18400	18400	18400	2480	5000
PWTR20.2RS	20	47	25	24	27	0,5	1,0	245	24600	31000	20600	31000	3800	3800
PWTR2052.2RS	20	52	25	24	27	0,5	1,0	321	27000	35500	31000	35500	4350	3800
PWTR25.2RS	25	52	25	24	31	0,5	1,0	281	25500	33500	21800	33500	4200	3800
PWTR2562.2RS	25	62	25	24	24	0,5	1,0	450	30000	42500	42500	42500	5300	3800
PWTR30.2RS	30	62	29	28	38	0,5	1,0	465	35000	46000	29000	46000	5900	2200
PWTR3072.2RS	30	72	29	28	38	0,5	1,0	697	41000	56000	54000	56000	7300	2200
PWTR35.2RS	35	72	29	28	44	0,6	1,1	630	39000	55000	38500	55000	7100	1800
PWTR3580.2RS	35	80	29	28	44	0,6	1,1	836	43500	65000	59000	65000	8300	1800
PWTR40.2RS	40	80	32	30	50,5	0,6	1,1	816	45000	62000	39500	62000	8000	1500
PWTR4090.2RS	40	90	32	30	50,5	0,6	1,1	1129	52000	77000	67000	77000	9800	1500
PWTR45.2RS	45	85	32	30	55,2	0,6	1,1	883	45500	64000	41000	64000	8400	1300
PWTR45100.2RS	45	100	32	30	55,2	0,6	1,1	1396	56000	86000	86000	86000	11100	1300
PWTR50.2RS	50	90	32	30	59,8	0,6	1,1	950	46000	67000	42000	67000	8700	1100
PWTR50110.2RS	50	110	32	30	59,8	0,6	1,1	1690	59000	95000	95000	95000	12300	1100